



2010 CHEVROLET CAMARO SPECIFICATIONS

Models: Chevrolet Camaro LS, LT and SS

Body style/driveline: four-passenger, front-engine, rear-drive coupe

Construction: unitized bodyframe, one- and two-sided galvanized steel

FPA vehicle class: Coupe

Manufacturing location: Oshawa, Ontario, Canada

Key competitors: Dodge Challenger, Ford Mustang, Nissan 350Z

ENGINES

3.6L V6 DI VVT (LLT) 6.2L V8 (LS3, L99)

Application: LS, LT SS 3.6L V6 Type: Displacement (cu in/cc): 217/3564

Bore & stroke (in/mm): 3.70 x 3.37/94 x 85.6

Block material: cast aluminum w/cast-in-place

iron bore liners

Cylinder head material: aluminum

Valvetrain: dual overhead camshafts, four

valves per cylinder, continuously

Variable Valve Timing

273/370 @ 5200 rpm1

Ignition system: electronic individual coil-on-plug;

individual cylinder knock control and extended-life platinum-tipped

spark plugs

Fuel delivery: direct high-pressure fuel injection

Compression ratio: 11.3:1

Horsepower (hp/kW @ rpm): 300/224 @ 6400 rpm1

(projected)

Torque (lb.-ft./Nm @ rpm):

(projected)

regular unleaded Recommended fuel:

7000

Maximum engine rpm:

Emissions controls: evaporative system, single close-

coupled catalytic converter, equallength exhaust, single underfloor catalytic converter, positive crankcase ventilation, intake and exhaust cam phasers, Electronic

Throttle Control

Fuel economy (auto trans): 27 hwy. (est.)

Based on GM testing. EPA estimates

not yet available.

Preproduction models shown. Actual production models may vary. Coupe available spring 2009. 1. Pending SAE certification.

6.2L V8

376/6162

4.06 x 3.62/103.25 x 92

cast aluminum w/cast-in-place

iron bore liners

aluminum

valve-in-head, two valves per cylinder, roller lifters, Active Fuel

Management (L99)

high-energy distributorless ignition, solid state direct-fire ignition w/coil-near-plug and integrated

returnless, multiport fuel injection

10.7:1

422/315 @ 5000 (LS3)1 400/299 @ 5000 (L99)¹

408/553 @ 4500 (LS3)1

395/535 @ 4500 (L99)1

premium unleaded

6000 (L99) 6600 (LS3)

23 hwy. (est.)

evaporative system, closecoupled catalytic converters. positive crankcase ventilation,

Electronic Throttle Control







TRANSMISSIONS

	Hydra-Matic 6L50 six-speed automatic (LS, LT) w/TAPshift controls	Hydra-Matic 6L80 six-speed automatic (SS) w/TAPshift controls	AISIN AY6 six-speed manual (LS, LT)	TR6060 six-speed manual (SS)
Gear ratios (:1):				
First:	4.07	4.03	4.48	3.01
Second:	2.37	2.36	2.58	2.07
Third:	1.55	1.53	1.63	1.43
Fourth:	1.16	1.15	1.19	1.00
Fifth:	0.85	0.85	1.00	0.84
Sixth:	0.67	0.67	0.75	0.57
Reverse:	3.06	3.06	3.67	3.28
Final drive ratio:	3.27	3.27	3.27	3.45

CHASSIS/SUSPENSION

double-ball-joint, multi-link strut; direct-acting stabilizer bar; Front:

progressive-rate coil springs with fully adjustable camber,

caster and toe

Rear: 4.5-link independent; progressive-rate coil springs over

shocks; stabilizer bar; fully adjustable camber and toe

variable-rate rack-and-pinion Steering type:

Steering ratio: 16.1:1 2.5

Steering wheel turns, lock-to-lock:

Turning circle, curb-to-curb (ft/m): 37.7/11.5

BRAKES

Type: four-wheel disc w/ABS; ventilated front and rear rotors;

> single-piston front calipers and single-piston alloy rear calipers (LS, LT); four-piston fixed Brembo aluminum front and

rear calipers (SS)

Rotor diameter, front (in/mm): LS, LT: 12.64/321

SS: 14/355

Rotor diameter, rear (in/mm): LS, LT: 12.4/315


SS: 14.4/365


Rotor thickness, front (in/mm): LS, LT: 1.18/30

SS: 1.26/32

Rotor thickness, rear (in/mm): LS, LT: 0.9/23

SS: 1.1/28







WHEELS/TIRES

LT

Wheel size and type: 18" x 7.5" steel* 18" x 7.5" aluminum* 19" x 8" aluminum*

inum* 20" x 8" aluminum (front)* um* 20" x 9" aluminum (rear)*

Tires: P245/55R18 all-season* P245/55R-18 all-season*

P245/50R-19 all-season*

P245/45R-20 summer

SS

all-season* (front)*

P275/40R-20 summer

(rear)*



DIMENSIONS EXTERIOR

 Wheelbase (in./mm):
 112.3/2852

 Overall length (in./mm):
 190.4/4836

 Overall width (in./mm):
 75.5/1918

 Overall height (in./mm):
 54.2/1377

 Track, front (in./mm):
 63.7/1618

 Track, rear (in./mm):
 64.1/1628 (L

x, rear (in./mm): 64.1/1628 (LS, LT) 63.7/1618 (SS)

Curb weight (lb/kg): 3750/1705 – LT w/automatic

3741/1700 – LT w/manual 3769/1713 – LS w/automatic 3780/1718 – LS w/manual 3913/1779 – SS w/automatic 3860/1755 – SS w/manual

Weight balance (% front/rear): 52/48



INTERIOR

Seating capacity (front/rear): 2/2

Headroom (in/mm): front: 37.4/950 rear: 35.3/897

front: 42.4/1077 rear: 29.9/757

Shoulder room (in/mm): front: 56.9/1444

rear: 42.5/1080

CAPACITIES

Capacities

Legroom (in/mm):

Cargo volume (cu. ft./L): 11.3/320
Fuel tank (approx. gal./L): 19/71.9
Engine oil (qt/L): 3.6L: 7.6/7.2
6.2L: 8.9/8.5

* Use only GM-approved wheel/tire combinations. See dealer for details

Note: Information shown is current at time of publication.

Preproduction models shown. Actual production models may vary. Coupe available spring 2009.

Description	LS Coupe 1LS Starting at \$22,995 ¹	LT Coupe 1LT Starting at \$24,6301	LT Coupe 2LT Starting at \$27,3301	SS Coupe 1SS Starting at \$30,995 ¹	SS Coupe 2SS Starting at \$34,1801		
Air bags: dual-stage frontal, thorax side-impact for driver and front passenger and head- curtain side-impact for front and rear occupants, includes Passenger Sensing System	S ²	S ²	S ²	S ²	S ²		
Air conditioning: single-zone manual		S	S	S	S		
Audio system: AM/FM stereo with CD-ROM, MP3 playback, music navigator and Graphic Information Display, includes outside temperature display		S	S	S	S		
Brakes: 4-wheel antilock, 4-wheel disc	S	S	S	S	S		
Center console: floor with armrest and auxiliary input jack	S	S	S	S	S		
Cruise control: electronic with set and resume speed, steering-wheel-mounted	S	S	S	S	S		
Daytime Running Lamps	S	S	S	S	S		
Dead pedal: driver	S	S	S	S	S		
Defogger: rear-window electric	S	S	S	S	S		
Door locks: power programmable with lockout protection	S	S	S	S	S		
Exhaust: dual-outlet stainless-steel with polished tips	S	S	S	S	S		
Glove box: lockable	S	S	S	S	S		
LATCH (Lower Anchors and Top Tethers for CHildren) system	S	S	S	S	S		
Lighting: front reading lamps, interior dome with illuminated entry and theatre dimming	S	S	S	S	S		
OnStar with one year of Safe & Sound Plan	S ³	S ³	S ³	S ³	S ³		
Power outlets: 2 auxiliary	S	S	S	S	S		
Remote Keyless Entry	S	S	S	S	S		
Seats: front Sport bucket, includes power recliners, adjustable head restraints and folding rear seat with trunk pass-through	S	S ⁴	S ⁴	S ⁴	S ⁴		
StabiliTrak® Stability Control System with Traction Control	S	S	S	S	S		
Steering: power, variable ratio	S	S	S	S	S		
Steering column: manual rake and telescopic	S	S	S	S	S		
Theft-deterrent system: PASS-Key III	S	S	S	S	S		
Tire Pressure Monitoring System	S	S	S	S	S		
Tire sealant and inflator kit	S	S	S	S	S		
Transmission: 6-speed manual	S	S	S	S	S		
Windows: power with driver and passenger express-down/up	S	S	S	S	S		
Wipers, front intermittent	S	S	S	S	S		
XM® Radio with 3 trial months	S ⁵	S⁵	S⁵	S ⁵	S⁵		
Foglamps		S ⁶	S ⁶	S ⁶	S ⁶		
Audio system feature: Boston Acoustics premium 9-speaker system, 245 watts		Α	S	А	S		
Bluetooth® wireless technology for select compatible phones		A ^{7,8}	S ⁸		S ⁸		
PDIM: wireless		A ⁷	S		S		
Steering-wheel-mounted audio controls		A ⁷	S		S		
USB port		A ⁷	S		S		
Cargo convenience net		A ⁷	S		S		
Gauges: 4 auxiliary, multifunction			S		S		
Mirror: inside rearview auto-dimming			S		S		
Mirrors: outside heated power-adjustable and driver side auto-dimming, body-color			S		S		
Seats: heated driver and front passenger			S		S		
Seat trim: leather-appointed front seats			S		S		
Universal Home Remote: includes garage door opener, 3-channel programmable			S		S		
Engine: 6.2L V8				S	S		
Four-piston Brembo® brakes				S	S		
Instrumentation: with SS detail				S	S		
Fascias: front and rear body-color, SS-specific, with unique front grille and rear diffuser, lower extension, front air scoop and brake cooling slots				S	S		
Sill plate: Chevrolet				S	S		
Spoiler: rear		A ⁹	A ⁹	S	S		
Tires: P245/45R20 front and P275/40R20 rear, summer tires				S ¹⁰	S ¹⁰		
Wheels: 20 x 8-inch front and 20 x 9-inch rear flangeless, painted aluminum with Sterling Silver finish (Midnight Silver finish when RS Appearance Package is ordered) S ¹⁰ S ¹⁰							

BE ONE OF THE FIRST TO TAKE THE WHEEL OF THIS TRULY MODERN PERFORMANCE CAR.

CHOOSE YOUR TRIM LEVEL, OPTIONS AND COLOR, THEN VISIT YOUR LOCAL CHEVY DEALER TO ORDER YOUR 2010 CAMARO BEGINNING OCTOBER 13.



- 1. MSRP. Tax, title, license and dealer fees extra. Optional equipment extra.
- 2. Always use safety belts and the correct child restraint for your child's age and size. Children are safer when properly secured in a rear seat in the appropriate infant, child or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active air bag. See the Owner's Manual and child safety seat instructions for more safety information.
- 3, Call 1-888-4ONSTAR (1-888-466-7827) and visit onstar.com for details and system limitations.
- 4. Includes passenger-side seatback map pocket.
- 5. XM Radio requires a subscription, sold separately after the first 90 days. Not available in Alaska or Hawaii. For more information, visit gm.xmradio.com.
- 6. When (WRS) RS Package is ordered, fog lamps act as Daytime Running Lamps.
- 7. Included and only available with (SRJ) Convenience and Connectivity Package.
- 8. The Bluetooth word mark is a registered trademark owned by Bluetooth SIG, Inc. and any use of such mark by Chevrolet is under license. Go to am.com/bluetooth to find out which Bluetooth phones are compatible with the
- 9. Included and only available with (WRS) RS Package.
- 10. Use only GM-approved wheel/tire combinations. See dealer for details.

GM, the GM Logo, Chevrolet, the Chevrolet Logo, and the slogans, emblems, vehicle model names, vehicle body designs and other marks appearing in this document are the trademarks and/or service marks of General Motors Corporation, it's subsidiaries, affiliates or licensors. OnStar is a registered service mark of OnStar Corp. Certain vehicle features may lose their usefulness over time due to obsolescence from technological changes. ©2008 General Motors Corporation, All rights reserved.

AVAILABLE OPTIONS

Description	LS Coupe 1LS	LT Coupe 1LT	LT Coupe 2LT	SS Coupe 1SS	SS Coupe 2SS
Engine block heater	Α	А	А		
Transmission, 6-speed automatic, electronically controlled with TAPshift® on steering wheel	А	А	А	A¹	A¹
Boston Acoustics® premium 9-speaker system, 245 watts		А	S	А	S
Convenience and Connectivity Package		A ²			
Floormats: carpeted front	А	S	S	S	S
Inferno Orange Interior Accent Trim Package			Α		A ³
Sunroof: power with express open and venting		А	А	А	А
RS Appearance Package		А	А	А	А
Spare wheel and tire: compact	А	А	А		
Wheels: 19-inch polished aluminum		А	А		
Wheels: 20" x 8" front and 20" x 9" rear polished aluminum				A ⁴	A ⁴
Cyber Gray Metallic Stripe Package			А		Α
White Stripe Package			Α		А
Red Jewel Tintcoat (Extra-cost color)		А	А	А	А



Product information is preliminary. Preproduction models shown. Actual production models may vary. Coupe available spring 2009.

- 1. SS includes L99 6.2L V8.
- 2. Also includes (BTV) remote vehicle starter system when (MXO) 6-speed automatic transmission is ordered.
- 3. Includes SS embroidery.
- 4. Use only GM-approved wheel/tire combinations. See dealer for details.



SILVER ICE METALLIC



INFERNO ORANGE METALLIC



VICTORY RED



CYBER GRAY METALLIC



BLACK



RED JEWEL TINT COAT
Extra-cost color



RALLY YELLOW



IMPERIAL BLUE METALLIC

Not available on SS



AQUA BLUE METALLIC Not available on SS



SUMMIT WHITE Interim availability